

- **Due Woofer 100mm in cabinet reflex**
- **Tweeter 20mm a cupola morbida**
- **Sistema di sospensione incluso**
- **Pilotaggio full range passivo**
- **Per installazioni permanenti**

LSS MIL100 è un diffusore acustico ideale per impianti di sonorizzazione distribuiti. MIL 100 può essere ideale per applicazioni audio video, sonorizzazioni di piccoli e medi locali, etc. I punti di aggancio compresi nel mobile facilitano la sospensione permanente in installazioni fisse.

- **Two 100mm Lf shielded in vented enclosure**
 - **20mm shielded Dome tweeter**
 - **Fly mounting points included**
 - **Powering mode full range passive**
 - **For permanent installations**
- The MIL100 system is ideal for distributed systems. It is ideal for sound reinforcement in A/V events in discobar, pubs multimedia halls etc. The comprehensive system mounting points permit safe, suspension in permanent installations.

MIL100

COMPACT 2-WAY LOUDSPEAKER SYSTEM



Product Information

LSS MIL100 è un diffusore acustico a due vie dalla linearità hi-fi e dall'affidabilità professionale è utilizzabile sia come sistema a gamma intera sia come satellite da accoppiare ad un sub woofer (es. PULCEW o SUB Sm1). MIL100 utilizza due mid woofer da 100 mm schermati e un Tweeter da 20mm a cupola morbida anch'esso schermato. Il crossover passivo a bassa tolleranza con pendenza 12db e il circuito di protezione Poliswitch garantiscono la massima affidabilità.

LSS's MIL100 2-way loudspeaker system is able to reproduce hi-fi-like professional sound. The bass reflex cabinet houses two 100 shield mid-woofer and one 20mm soft dome shield tweeter. This loudspeakers, is designed to work in full range mode or to be supported by the PULCEW subwoofer below 100 Hz



LSS Advanced Speakers Systems

Via On. Longo 53 - 89024 Polistena (RC) ITALY
Tel. (39) 966 932199 - Fax (39) 966 933007
Email: lss@lss.it - Internet: www.lss.it

www.lss.it

MIL100

Dimensions

COMPACT 2-WAY LOUDSPEAKER SYSTEM

Data Sheet

Physical

Dimensions mm (± 1 mm)

- Height 160
- Width 450
- Depth 226

Weights Kilograms

- Net Weight 5
- Shipping Weight 6
- System Configuration **2way full range**

Enclosure Material

- Enclosure material **MDF of 14mm**
- Finish **Texture poliuretanic black paint**
- Suspension **4 point mounting suspension**
- Grille **Poweder coated perforated steel**
- Connectors **Black and Red Clamps**
- Optional Accessories **Fly clip with ring**

Performance

Frequency Response

- ± 5 dB 80Hz to 20Kz
- -10 dB 65Hz

Sensitivity (dB 1 watt @ 1 m)

- Full Range Passive **90dB**
- LF **89dB**
- HF **91dB**

Nominal Input Impedance (ohms)

- Full Range Passive **8**
- LF **16**
- HF **8**

Power Handling (watts cont. AES)

- Full Range Passive **120**
- LF **100**
- HF **50**

SPL (referenced to 1 m 1w)


- Full Range Passive **90dB**

Nominal Dispersion (degrees @ - 6 dB)

- Horizontal **90°**
- Vertical **45°**

- Product Series MIL
- LF Subsystem & Loading Two **100mm woofer shielded vented**
- HF Subsystem & Loading **One 20mm dome shielded Tweeter**
- Crossover 2 way **12/12dB**
- Sistem Protection Poliswitch

Additional Date



LSS Advanced Speakers Systems

Via On. Longo 53 - 89024 Polistena (RC) ITALY
Tel. (39) 966 932199 - Fax (39) 966 933007
Email: lss@lss.it - Internet: www.lss.it