

WM2

ULTRA LOW PROFILE STAGE MONITOR SYSTEM



- 12" Coax Neodymium Transducer in Vented Enclosure
- Modified exponential rotatable horn with controlled coverage
- Flying Mounting Points and Pole Mount Cup Included
- Powering Mode: Full-Range Passive
- For Portable Use or Permanent Installation

Product Information

2-WAY loudspeaker is ideal for stage monitor applications high output vocal presence and neutral balanced sound. The 300 mm (12") low frequency cone with 75 mm (3") voice coil with Neodymium magnet and 72 mm (2.8") voice coil high frequency compression driver provide higher output and lower distortion plus enhanced power handling capabilities for better performance in both touring and permanently installed applications. LSS's advanced crossover includes professional protection of HF. Powering mode full range passive. WM2 is designed to support the widest possible range of pro audio applications. The pole mount cup provide front or side fill for touring applications.

Data Sheet

Frequency Response	±5 dB 65 Hz ~ 18 kHz -10 dB 50 Hz
Sensitivity (1 Watt @ 1 m)	98 dB
Max SPL Calculated (Power AES) [PEAK]	126 dB [131 dB]
Nominal Input Impedance (Ω)	8 Ω
Power Handling (Watts Cont. AES) [PEAK]	600 W [1800 W]
Nominal Dispersion (@ -6 dB)	60°(H) x 40°(V) Rotatable Horn
Dimensions mm (±1 mm) (H x W x D)	315 x 500 x 485
Weight	16,5 Kg

Enclosure Material

- Enclosure Material: Birch Plywood of 15 mm
- Finish: Texture Polyurethane Black Paint
- Suspension: 6 Point Mounting Suspension
- Grille: Powder Coated Perforated Steel with anti-dust foam
- Connectors: 4 Neutrik NL4 Speakon
- Optional Accessories: Fly Clip with Ring, Flight Case for 2 WM2

INSTALL | EVENTS | PORTABLE | TOURING

