M60

MULTIFUNCTION COMPACT HIGH POWER SYSTEM



- 14" LF Neodymium Driver with 3.5" Voice Coil in Vented Enclosure
- 3" Compression driver with Rotable 1.4" Horn
- Fly Mounting Points
- Powering Mode: Full-Range Passive
- For Touring or Permanent Installation

Product Information

M60 is a 2-WAY fullrange multifunction loudspeaker ideal for a main speaker for live event, as a delay line speaker, for voice reinforcement or as a monitor stage.

The pilotage is fullrange passive. The system works alone for small event or coupled with a LSS sub woofer.

The system uses one 360 mm (14") long excursion woofer with Neodymium magnet and voice coil of 88mm and a (3,5"), Titanium 75mm (3") Neodymium driver coupled to a rotable Aluminium 1.4" horn.

The passive crossover with HF protection circuit ensure high pressures and maximum reliability.

The mounting points included in the cabinet offer the possibility of suspension.

Data Sheet

Frequency Response $\pm 5 \text{ dB } 80 \text{ Hz} \sim 20 \text{ KH}$ -10 dB 65 Hz	iz
---	----

Sensitivity (1 Watt @ 1 m) 99 dB

128 dB Max SPL Calculated (Power AES) [PEAK] [132 dB]


Nominal Input Impedance (Ω) 8Ω

Power Handling (Watts Cont. AES) 800 W [2000 W] [PEAK]

Nominal Dispersion (@ -6 dB) 80° (H) x 60° (V)

Dimensions mm (±1 mm) 684 x 428,5 x 370 $(H \times W \times D)$


28 Kg





Enclosure Material

- Enclosure Material: Birch Plywood of 18 mm
- Finish: Texture Polyurethane Black Paint
- Suspension: 6 Point Mounting Suspension
- Grille: Powder Coated Perforated Steel with anti-dust foam
- Connectors: 4 Neutrik NL4 Speakon
- Optional Accessories: Adjustable Speaker Mount Braket, Speaker Soft Bag

INSTALL | EVENTS | PORTABLE | MONITOR









MULTIFUNCTION COMPACT HIGH POWER SYSTEM

M60

