

SP110

COMPACT 2-WAY LOUDSPEAKER SYSTEM



- 4" LF in Vented Enclosure
- 1,1" Silk Soft Dome Tweeter
- Fly Mounting Points and U bracketed Included
- Powering Mode: Full Range Passive
- For Permanent Installation

Product Information

2-WAY loudspeaker system is the first small enclosure to the SP Series. This speaker is able to reproduce Hi-Fi like professional sound. The bass reflex trapezoidal cabinet houses one 100 mm (4") mid-woofer and one 28 mm (1.1") silk soft dome tweeter. This loudspeaker is designed to work in full range mode or to be supported by the PULCE-W subwoofer below 100 Hz.

Data Sheet

Frequency Response	± 5dB 80 Hz to 20 KHz -10 dB 65 Hz
--------------------	---------------------------------------

Sensitivity (1 Watt @ 1 m)	90 dB
----------------------------	-------

Max SPL Calculated (Power AES) [PEAK]	108 dB [112 dB]
---------------------------------------	--------------------

Nominal Input Impedance (Ω)	8 Ω
-----------------------------	-----

Power Handling (Watts Cont. AES) [PEAK]	70 W [175 W]
---	-----------------

Nominal Dispersion (@ -6 dB)	90° (H) x 100° (V)
------------------------------	--------------------

Dimensions mm (±1 mm) (H x W x D)	270 x 150 x 170
--------------------------------------	-----------------

Weight	2,3 Kg
--------	--------

Enclosure Material

- Enclosure Material: MDF of 14 mm
- Finish: Texture Polyurethane Black Paint
- Suspension: 3 Point Mounting Suspension M6 and U bracket System Included
- Grille: Powder Coated Perforated Steel with anti-dust foam
- Connectors: Black and Red ClampsNeutrik NL4 Speakon
- Optional Accessories: Flight Clip with Ring

INSTALL | EVENTS

