

SP216

COMPACT 2-WAY LOUDSPEAKER SYSTEM



- 6" LF in Vented Enclosure
- 1" Compression driver with Conical Horn
- Fly Mounting Points aIncluded
- Powering Mode: Full Range Passive
- For Permanent Installation

Product Information

2-WAY loudspeaker system uses one 160 mm (6") mid-woofer with 38 mm (1.5") voice coil and one 26 mm (1") driver on conical horn. SP216 is ideal for medium and smaller Clubs, Dance floors. The cabinet offers built-in flying points for both horizontal and vertical mounting. The trapezoidal cabinet allows flexible fixing in low ceiling venues or easy construction of clusters and arrays. The system provides high output, low distortion sound reinforcement. The internal passive crossover of 12dB/Octave and Poliswitch protection offers better performance in and permanently installed applications.

Data Sheet

Frequency Response	±5 dB 70 Hz ~ 20 KHz -10 dB 60 Hz
--------------------	--------------------------------------

Sensitivity (1 Watt @ 1 m)	92 dB
----------------------------	-------

Max SPL Calculated (Power AES) [PEAK]	112dB [116dB]
---------------------------------------	------------------

Nominal Input Impedance (Ω)	8 Ω
-----------------------------	-----

Power Handling (Watts Cont. AES) [PEAK]	100 W [250 W]
---	------------------

Nominal Dispersion (@ -6 dB)	80° (H) x 80° (V)
------------------------------	-------------------

Dimensions mm (±1 mm) (H x W x D)	335 x 240 x 273
--------------------------------------	-----------------

Weight	6,5 Kg
--------	--------

Enclosure Material

- Enclosure Material: MDF of 14 mm
- Finish: Texture Polyurethane Black Paint
- Suspension: 3 Point Mounting Suspension M6 and U Bracket System Included
- Grille: Powder Coated Perforated Steel with anti-dust foam
- Connectors: Black and Red Clamps
- Optional Accessories: Fly Clip with Ring

INSTALL | EVENTS | PORTABLE

