

SUBDRIVE12A

COMPACT SELF POWERED SUBWOOFER SYSTEM



Product Information

SUBDRIVE12A is a reflex subwoofer that uses a loudspeaker of 320 mm (12") with Neodymium magnet and 100 mm (4") Fiberglass support of coil. Low distortion and high dynamic distinguish this product. The cabinet is constructed from birch plywood of 15 mm anti stretch polyurethane finished. SUBDRIVE12A has a Digital Amplifier and switching power supply from 1500 W for the sub and DSP module integrated and active stereo out for satellites of 350W + 350W. It is possible to choice within 4 different preset stored by default.

Enclosure Material

- Enclosure Material: Birch Plywood of 15 mm
- Finish: Texture Polyurethane Black Paint
- Suspension: 1 Pole Mount Cup
- Grille: Powder Coated Perforated Steel with anti-dust foam
- Connectors: Neutrik XLR In & Out + Out for Sat Neutrik NL4 Speakon
- AC Power: 240V, Powercon In & Out
- Optional Accessories: Soft Cover

INSTALL | EVENTS | LIVE | PORTABLE

- 12" Neodymium LF Subwoofer
- High Dynamic Bass Response Subwoofer System for Mini Live PA and any Other Events
- Pole Mount Cup Included
- Powering Mode: Self-Powered with 1500 W Digital Power Module for the SUB and 350 W + 350 W for the satellites with stored four preset
- For Portable Use or Permanent Installation

Data Sheet

Frequency Response	±5 dB 40 Hz ~ 180 Hz -10 dB 35 Hz
Sensitivity (1 Watt @ 1 m)	95 dB
Max SPL Calculated (Power EIAJ) [PEAK]	127 dB [130 dB]
Nominal Input Impedance (Ω)	8 Ω
Power Handling (Watts EIAJ) [PEAK]	1500 W [3000 W] 350W+350W [700W+700W]
Nominal Dispersion (@ -6 dB)	360°
Dimensions mm (±1 mm) (H x W x D)	400 x 500 x 450
Weight	27 Kg

