

SUBDRIVE12P

COMPACT SUBWOOFER SYSTEM



- 12" Neodymium LF Subwoofer
- High Dynamic Bass Response Subwoofer System for Mini Live PA and any Other Events
- Pole Mount Cup Included
- For Portable Use or Permanent Installation

Product Information


SUBDRIVE12 is a band-pass subwoofer that uses a loudspeaker of 320 mm (12") with Neodymium magnet and 100 mm (4") coil. Low distortion and high dynamic distinguish this product. The cabinet is constructed from birch plywood of 15 mm and anti stretch polyurethane finished. SUBDRIVE12 is a reflex subwoofer designed to reinforce the extremely low range frequency of small portable equipment in live music or small installations in disco bar, pub etc. The cabinet extremely compact makes it easily transportable and versatile for portable applications. SUBDRIVE12 surprises for his big punch and high dynamic response at the extreme low frequency.

Data Sheet

Frequency Response	±5 dB 50 Hz ~ 180 Hz -10 dB 40 Hz
Sensitivity (1 Watt @ 1 m)	93 dB
Max SPL Calculated (Power AES) [PEAK]	123 dB [130 dB]
Nominal Input Impedance (Ω)	8 Ω
Power Handling (Watts Cont. AES) [PEAK]	1000 W [5000 W]
Nominal Dispersion (@ -6 dB)	360°
Dimensions mm (±1 mm) (H x W x D)	400 x 500 x 450
Weight	25 Kg

Enclosure Material

- Enclosure Material: Birch Plywood of 15 mm
- Finish: Texture Polyurethane Black Paint
- Suspension: 1 Pole Mount Cup
- Connectors: 2 Neutrik NL4 Speakon
- Optional Accessories: Soft Cover



INSTALL | EVENTS | LIVE | PORTABLE